


# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### PRODUCT PHOTOGRAPH




### GENERAL INFORMATION

Product Code	9540311
Product Category	Downlights-Commercial
Product Family	Dine
Mounting Location	Ceiling
Application Environment	Outdoor

### DIMENSION & WEIGHT

LxWxH (cm)	D:14.5 H:5.3
Cut out (cm)	12,5
Weight (Kgr)	0,4

### TECHNICAL DRAWING



### MATERIAL & COLOR

Product Color	White
Body Material	Aluminium
Cover Material	N/A

### APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP54
Protection Class IK	IK04
Dimmable	Yes
Type of Dimming (Optional)	Triac/Dali
Mounting type	Recessed
Mounting Depth (cm)	Ceiling
Led Module Replaceable	No
Light Source	Led
Adjustable	No

### COMPATIBLE WITH

— On/Off Driver: Included

— Triac Driver: 9844002, 9540319

— Dali Driver: 9621523

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



# NOVA LUCE

## PRODUCT DATASHEET

Version: 001

### ELECTRICAL DATA

Power (Nominal)	<b>18</b>
Input voltage (Nominal)	<b>220-240Vac</b>
Mains Frequency	<b>50/60Hz</b>
Output voltage	<b>40Vdc</b>
Output Current	<b>450mA</b>
Power Factor	<b>0,9</b>
Efficiency	<b>ò88%</b>
SVM	<b>?0.4</b>
Pst	<b>?1</b>
Class	<b>II</b>

### PHOTOMETRICAL DATA

Luminus Flux	<b>2094</b>
Luminous Efficacy	<b>116.3</b>
Color Temperature	<b>3000/4000/5000</b>
Light Color (Designation)	<b>Dip-Switch</b>
CRI	<b>&gt;80</b>
SDCM	<b>&lt;3</b>
Beam Angle	<b>90</b>
UGR	<b>N/A</b>

### LIFESPAN

Lifetime	<b>50000</b>
----------	--------------

### CERTIFICATES

Certificates	<b>CE ROHS</b>
--------------	----------------

### WARRANTY

Warranty	<b>5 Years</b>
----------	----------------

### LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com

