

# NOVA LUCE


PRODUCT DATASHEET

Version: 001

## PRODUCT PHOTOGRAPH



## TECHNICAL DRAWING



## COMPATIBLE WITH

— On/Off Driver: Included

— Triac Driver: 9844008(Remote)

— Dali Driver: 9621523

## GENERAL INFORMATION

Product Code	9232212
Product Category	Downlights
Product Family	Dust
Mounting Location	Ceiling
Application Environment	Outdoor

## DIMENSION & WEIGHT

LxWxH (cm)	D:5.5 H:7
Cut out (cm)	4,6
Weight (Kgr)	N/A

## MATERIAL & COLOR

Product Color	White
Body Material	Aluminium
Cover Material	N/A

## APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP65
Protection Class IK	IK04
Dimmable	Yes
Type of Dimming (Optional)	Triac/Dali
Mounting type	Recessed
Mounting Depth (cm)	Ceiling
Led Module Replaceable	No
Light Source	Led
Adjustable	No

NOVA LUCE S.A

Schimatari Viotias  
32009, Greece

+30 22620 58 121  
+30 22620 56 743

info@novaluce.com  
www.novaluce.com



## ELECTRICAL DATA

Power (Nominal)	<b>9</b>
Input voltage (Nominal)	<b>220-240Vac</b>
Mains Frequency	<b>50/60Hz</b>
Output voltage	<b>N/A</b>
Output Current	<b>N/A</b>
Power Factor	<b>N/A</b>
Efficiency	<b>N/A</b>
SVM	<b>N/A</b>
Pst	<b>N/A</b>
Class	<b>II</b>

## PHOTOMETRICAL DATA

Luminous Flux	<b>557</b>
Luminous Efficacy	<b>61.9</b>
Color Temperature	<b>3000</b>
Light Color (Designation)	<b>Warm White</b>
CRI	<b>&gt;90</b>
SDCM	<b>&lt;3</b>
Beam Angle	<b>24</b>
UGR	<b>&lt;17</b>

## LIFESPAN

Lifetime	<b>30000</b>
----------	--------------

## CERTIFICATES

Certificates	<b>CE, UKCA</b>
--------------	-----------------

## WARRANTY

Warranty	<b>5 Years</b>
----------	----------------

## LIGHT DISTRIBUTION

